

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK

1. PRODUCT AND COMPANY IDENTIFICATION

Dow Corning Corporation
South Saginaw Road
Midland, Michigan 48686

24 Hour Emergency Telephone: (989) 496-5900

Customer Service: (989) 496-6000

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 04040697

Revision Date: 2010/03/19

Generic Description: Sealant.

Physical Form: Paste

Color: Charcoal gray

Odor: Alcoholic odor

NFPA Profile: Health 1 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTSAcute Effects

Eye: Direct contact may cause moderate irritation. Vapor may cause eye irritation.

Skin: May cause mild irritation. Overexposure may cause drowsiness, dizziness, confusion or loss of coordination due to skin absorption.

Inhalation: Vapor may irritate nose and throat. Overexposure by inhalation may cause drowsiness, dizziness, confusion or loss of coordination.

Oral: May cause vomiting. Overexposure by ingestion may cause drowsiness, dizziness, confusion or loss of coordination.

Prolonged/Repeated Exposure Effects

Skin: Overexposure by skin absorption may injure the following organ(s): Blood.

Inhalation: Overexposure by inhalation may injure the following organ(s): Blood.

Oral: Overexposure by ingestion may injure the following organ(s): Blood. Testes.

Other Health Effects

This product contains a chemical(s) that has the following effect(s):
Reproductive Toxicity
Carcinogenicity

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 2 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK

See Section 11 for specific details.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
16753-62-1	1.0 - 5.0	Methylvinyl dimethoxysilane
156145-66-3	1.0 - 5.0	Methylvinyl di(MIBKO)silane
279250-16-7	1.0 - 5.0	Methylacetoacetate t-butanol titanium complexes
68186-85-6	<=0.2	C.I. Pigment Green 50

The above components are hazardous as defined in 29 CFR 1910.1200.

4. FIRST AID MEASURES

Eye:	Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 - 20 minutes while holding the eyelid(s) open. If contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.
Skin:	As quickly as possible remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Immediately flush with lukewarm gently flowing water for 15 minutes. Completely decontaminate clothing, shoes and leather goods before reuse or discard. Obtain medical attention.
Inhalation:	Remove from the source of contamination or move to fresh air. Obtain medical attention.
Oral:	Never give anything by mouth if victim is rapidly losing consciousness or convulsing. DO NOT INDUCE VOMITING. Have victim drink 2 to 8 oz. (60 to 240 mL) of water. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Have victim rinse mouth with water again. Immediately obtain medical attention.

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 3 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK

Notes to Physician: Treat according to person's condition and specifics of exposure.

5. FIRE FIGHTING MEASURES

Flash Point: Not applicable.

Autoignition Temperature: Not determined.

Flammability Limits in Air: Not determined.

Extinguishing Media: On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO₂), dry chemical or water spray. Water can be used to cool fire exposed containers.

Fire Fighting Measures: Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Unusual Fire Hazards: None.

6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. Product evolves flammable methyl alcohol when exposed to water or humid air. Provide ventilation during use to control exposure within Section 8 guidelines or use air-supplied or self-contained breathing apparatus. Product evolves methyl isobutyl ketoxime (MIBKO) when exposed to water or humid air. Use respiratory protection and/or provide ventilation during use to control methyl isobutyl ketoxime (MIBKO) exposure. Avoid eye exposure. Avoid skin contact. Avoid breathing vapor, mist, dust, or fumes. Keep container closed. Do not take internally.

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 4 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Component Exposure Limits**

<u>CAS Number</u>	<u>Component Name</u>	<u>Exposure Limits</u>
16753-62-1	Methylvinyl dimethoxysilane	See methyl alcohol comments.
156145-66-3	Methylvinyl di(MIBKO)silane	See methyl isobutyl ketoxime comments.
279250-16-7	Methylacetoacetate t-butanol titanium complexes	Observe titanium dioxide limits. OSHA PEL (final rule): TWA 15 mg/m ³ and ACGIH TLV: TWA 10 mg/m ³ .
68186-85-6	C.I. Pigment Green 50	Observe limits: Nickel - OSHA PEL and ACGIH TLV: TWA 1 mg/m ³ . Cobalt - OSHA PEL (final rule) and ACGIH TLV: TWA 0.05 mg/m ³ .

Methyl alcohol forms on contact with water or humid air. Provide adequate ventilation to control exposures within guidelines of OSHA PEL: TWA 200 ppm and ACGIH TLV-skin: TWA 200 ppm, STEL 250 ppm. Methyl isobutyl ketoxime is formed upon contact with water or humid air. Provide adequate ventilation to control exposures. Exposure limits have not yet been established.

Engineering Controls

Local Ventilation: Recommended.
General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Avoid skin contact by implementing good industrial hygiene practices and procedures. Select and use gloves and/or protective clothing to further minimize the potential for skin contact. Consult with your glove and/or personnel protective equipment manufacturer for selection of appropriate compatible materials.

Inhalation: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. IH personnel can assist in judging the adequacy of existing engineering controls.

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 5 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK

Suitable Respirator: General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Personal Protective Equipment for Spills

Eyes: Use full face respirator.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Inhalation/Suitable Respirator: Respiratory protection recommended. Follow OSHA Respirator Regulations (29 CFR 1910.134) and use NIOSH/MHSA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Precautionary Measures: Avoid eye exposure. Avoid skin contact. Avoid breathing vapor, mist, dust, or fumes. Keep container closed. Do not take internally. Use reasonable care.

Comments: Product evolves flammable methyl alcohol when exposed to water or humid air. Provide ventilation during use to control exposure within Section 8 guidelines or use air-supplied or self-contained breathing apparatus. Product evolves methyl isobutyl ketoxime (MIBKO) when exposed to water or humid air. Use respiratory protection and/or provide ventilation during use to control methyl isobutyl ketoxime (MIBKO) exposure.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste
Color: Charcoal gray
Odor: Alcoholic odor
Specific Gravity @ 25°C: 1.43
Viscosity: Not determined.
Freezing/Melting Point: Not determined.
Boiling Point: Not determined.
Vapor Pressure @ 25°C: Not determined.
Vapor Density: Not determined.
Solubility in Water: Not determined.
pH: Not determined.
Volatile Content: 4 %
Flash Point: Not applicable.
Autoignition Temperature: Not determined.

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 6 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK

Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors to form as described in Section 8.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Metal oxides. Formaldehyde. Silicon dioxide. Nitrogen oxides. Sulfur oxides.

11. TOXICOLOGICAL INFORMATION

Component Toxicology Information

Inhalation of fumes may result in metal fume fever, a flu-like illness with symptoms of metallic taste, fever and chills, aches, chest tightness, and cough.

May produce blood effects, reducing the bloods' ability to transport oxygen (methemoglobinemia and anemia).

Special Hazard Information on Components**Carcinogens**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
68186-85-6	<=0.2	C.I. Pigment Green 50

IARC Group 2B - Possibly Carcinogenic to Humans.
Cobalt compound.

Reproductive Toxicity

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 7 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK

CAS Number	Wt %	Component Name
------------	------	----------------

156145-66-3	1.0 - 5.0	Methylvinyl di(MIBKO)silane
-------------	-----------	-----------------------------

Evidence of reproductive effects in laboratory animals.

12. ECOLOGICAL INFORMATION

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS

RCRA Hazard Class (40 CFR 261)

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION

DOT Road Shipment Information (49 CFR 172.101)

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

**DOW CORNING CORPORATION
Material Safety Data Sheet**

Page: 8 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK**Air Shipment (IATA)**

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings**Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):Acute: Yes
Chronic: Yes
Fire: No
Pressure: No
Reactive: No**Section 313 Toxic Chemicals (40 CFR 372):**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
68186-85-6	<=0.2	C.I. Pigment Green 50

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

Supplemental State Compliance Information**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

Massachusetts

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 9 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 70.0	Calcium carbonate
1333-86-4	<=4.8	Carbon black
13463-67-7	<=4.6	Titanium dioxide

New Jersey

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 70.0	Calcium carbonate
PMN871176	30.0 - 60.0	Dimethyl siloxane, trimethoxysilyl-terminated
70131-67-8	7.0 - 13.0	Dimethyl siloxane, hydroxy-terminated
147-14-8	<=7.4	Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (Pigment blue 15)
63148-62-9	<=7.4	Polydimethylsiloxane
1333-86-4	<=4.8	Carbon black
13463-67-7	<=4.6	Titanium dioxide
68186-85-6	<=0.2	C.I. Pigment Green 50

Pennsylvania

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
471-34-1	40.0 - 70.0	Calcium carbonate
PMN871176	30.0 - 60.0	Dimethyl siloxane, trimethoxysilyl-terminated
70131-67-8	7.0 - 13.0	Dimethyl siloxane, hydroxy-terminated
147-14-8	<=7.4	Tetrabenzo-5,10,15,20-diazaporphyrinephthalocyanine (Pigment blue 15)
63148-62-9	<=7.4	Polydimethylsiloxane
1333-86-4	<=4.8	Carbon black
13463-67-7	<=4.6	Titanium dioxide

**DOW CORNING CORPORATION
Material Safety Data Sheet**

Page: 10 of 10

Version: 2.3

Revision Date: 2010/03/19

DOW CORNING(R) 756 SMS BUILDING SEALANT BLACK**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark