

DOW CORNING**DOW CORNING CORPORATION**
Material Safety Data Sheet

Page: 1 of 8

Version: 6.0

Revision Date: 2010/06/16

DOW CORNING(R) 995 SILICONE STRUCTURAL SEALANT, BLACK**1. PRODUCT AND COMPANY IDENTIFICATION**Dow Corning Corporation
South Saginaw Road
Midland, Michigan 48686**24 Hour Emergency Telephone: (989) 496-5900**

Customer Service: (989) 496-6000

Product Disposal Information: (989) 496-6315

CHEMTREC: (800) 424-9300

MSDS No.: 02122197

Revision Date: 2010/06/16

Generic Description: Silicone elastomer

Physical Form: Paste

Color: Black

Odor: Alcoholic odor

NFPA Profile: Health 1 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

2. HAZARDS IDENTIFICATION**POTENTIAL HEALTH EFFECTS****Acute Effects**

Eye: Direct contact may cause mild irritation. Vapor may cause eye irritation.

Skin: May cause mild irritation.

Inhalation: Irritates respiratory passages very slightly.

Oral: Low ingestion hazard in normal use.

Prolonged/Repeated Exposure Effects

Skin: No known applicable information.

Inhalation: No known applicable information.

Oral: No known applicable information.

Signs and Symptoms of Overexposure

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions.

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 2 of 8

Version: 6.0

Revision Date: 2010/06/16

DOW CORNING(R) 995 SILICONE STRUCTURAL SEALANT, BLACK

component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

| <u>CAS Number</u> | <u>Wt %</u> | <u>Component Name</u> |
|-------------------|-------------|---|
| 27858-32-8 | 1.0 - 5.0 | Diisopropoxy di(ethoxyacetoacetyl) titanate |

The above components are hazardous as defined in 29 CFR 1910.1200.

4. FIRST AID MEASURES

| | |
|---------------------|--|
| Eye: | Remove from the source of contamination or move to fresh air Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 5 minutes while holding the eyelid(s) open. Obtain medical attention. |
| Skin: | No health effects expected. If irritation does occur flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice. |
| Inhalation: | If symptoms are experienced remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice. |
| Oral: | If irritation or discomfort occur, obtain medical advice. |
| Notes to Physician: | Treat according to person's condition and specifics of exposure. |

5. FIRE FIGHTING MEASURES

| | |
|-----------------------------|---|
| Flash Point: | Not applicable. |
| Autoignition Temperature: | Not determined. |
| Flammability Limits in Air: | Not determined. |
| Extinguishing Media: | On large fires use dry chemical, foam or water spray. On small fires use carbon dioxide (CO ₂), dry chemical or water spray. Water can be used to cool fire exposed containers. |
| Fire Fighting Measures: | Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool. |
| Unusual Fire Hazards: | None. |

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 3 of 8

Version: 6.0

Revision Date: 2010/06/16

DOW CORNING(R) 995 SILICONE STRUCTURAL SEALANT, BLACK

6. ACCIDENTAL RELEASE MEASURES

Containment/Clean up: Observe all personal protection equipment recommendations described in Sections 5 and 8. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Note: See section 8 for Personal Protective Equipment for Spills. Call (989) 496-5900, if additional information is required.

7. HANDLING AND STORAGE

Use with adequate ventilation. Product evolves isopropyl alcohol when exposed to water or humid air. Provide ventilation during use to control exposure within guidelines or use respiratory protection. Avoid eye exposure. Avoid skin contact.

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

| <u>CAS Number</u> | <u>Component Name</u> | <u>Exposure Limits</u> |
|-------------------|---|---------------------------------|
| 27858-32-8 | Diisopropoxy di(ethoxyacetoacetyl) titanate | See isopropyl alcohol comments. |

Isopropyl alcohol is formed on contact with water or humid air. Provide adequate ventilation to control exposures to within exposure guidelines of OSHA PEL (final rule): TWA 400 ppm, 980 mg/m³ and ACGIH TLV: TWA 200 ppm, STEL 400 ppm.

Engineering Controls

Local Ventilation: None should be needed.
General Ventilation: Recommended.

Personal Protective Equipment for Routine Handling

Eyes: Use chemical worker's goggles.

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 4 of 8

Version: 6.0

Revision Date: 2010/06/16

DOW CORNING(R) 995 SILICONE STRUCTURAL SEALANT, BLACK

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves: Handle in accordance with good industrial hygiene and safety practices.

Inhalation: No respiratory protection should be needed.

Suitable Respirator: None should be needed.

Personal Protective Equipment for Spills

Eyes: Use chemical worker's goggles.

Skin: Wash at mealtime and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Inhalation/Suitable Respirator: No respiratory protection should be needed.

Precautionary Measures: Avoid eye exposure. Avoid skin contact. Use reasonable care.

Comments: Product evolves isopropyl alcohol when exposed to water or humid air. Provide ventilation during use to control exposure within guidelines or use respiratory protection.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Form: Paste
Color: Black
Odor: Alcoholic odor
Specific Gravity @ 25°C: 1.33
Viscosity: Not determined.
Freezing/Melting Point: Not determined.
Boiling Point: Not determined.
Vapor Pressure @ 25°C: Not determined.
Vapor Density: Not determined.
Solubility in Water: Not determined.
pH: Not determined.
Volatile Content: Not determined.
Flash Point: Not applicable.
Autoignition Temperature: Not determined.
Flammability Limits in Air: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 5 of 8

Version: 6.0

Revision Date: 2010/06/16

DOW CORNING(R) 995 SILICONE STRUCTURAL SEALANT, BLACK

specifications.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

Materials to Avoid: Oxidizing material can cause a reaction. Water, moisture, or humid air can cause hazardous vapors to form as described in Section 8.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Formaldehyde. Metal oxides. Sulfur oxides.

11. TOXICOLOGICAL INFORMATION

Special Hazard Information on Components

No known applicable information.

12. ECOLOGICAL INFORMATION

Environmental Fate and Distribution

Complete information is not yet available.

Environmental Effects

Complete information is not yet available.

Fate and Effects in Waste Water Treatment Plants

Complete information is not yet available.

Ecotoxicity Classification Criteria

| Hazard Parameters (LC50 or EC50) | High | Medium | Low |
|----------------------------------|------------|------------------------|---------|
| Acute Aquatic Toxicity (mg/L) | ≤ 1 | >1 and ≤ 100 | >100 |
| Acute Terrestrial Toxicity | ≤ 100 | >100 and ≤ 2000 | >2000 |

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 6 of 8

Version: 6.0

Revision Date: 2010/06/16

DOW CORNING(R) 995 SILICONE STRUCTURAL SEALANT, BLACK

section concerning the overall ecological safety of this material.

13. DISPOSAL CONSIDERATIONS**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal. Call (989) 496-6315, if additional information is required.

14. TRANSPORT INFORMATION**DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

Ocean Shipment (IMDG)

Not subject to IMDG code.

Air Shipment (IATA)

Not subject to IATA regulations.

Call Dow Corning Transportation, (989) 496-8577, if additional information is required.

15. REGULATORY INFORMATION

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

EPA SARA Title III Chemical Listings**Section 302 Extremely Hazardous Substances (40 CFR 355):**

None.

Section 304 CERCLA Hazardous Substances (40 CFR 302):

None.

Section 311/312 Hazard Class (40 CFR 370):Acute: No
Chronic: No
Fire: No

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 7 of 8

Version: 6.0

Revision Date: 2010/06/16

DOW CORNING(R) 995 SILICONE STRUCTURAL SEALANT, BLACK

Pressure: No
Reactive: No**Section 313 Toxic Chemicals (40 CFR 372):**

None present or none present in regulated quantities.

Note: Chemicals are listed under the 313 Toxic Chemicals section only if they meet or exceed a reporting threshold.

Supplemental State Compliance Information**California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

Massachusetts

| <u>CAS Number</u> | <u>Wt %</u> | <u>Component Name</u> |
|-------------------|-------------|-----------------------|
| 471-34-1 | <=42.0 | Calcium carbonate |
| 1333-86-4 | <=1.1 | Carbon black |

New Jersey

| <u>CAS Number</u> | <u>Wt %</u> | <u>Component Name</u> |
|-------------------|-------------|---|
| PMN871176 | <=45.0 | Dimethyl siloxane, trimethoxysilyl-terminated |
| 471-34-1 | <=42.0 | Calcium carbonate |
| None | <=41.0 | Calcium carbonate treated with stearic acid |
| 68083-19-2 | <=6.2 | Dimethyl siloxane, dimethylvinyl-terminated |
| 70131-67-8 | 1.0 - 5.0 | Dimethyl siloxane, hydroxy-terminated |
| 1333-86-4 | <=1.1 | Carbon black |

Pennsylvania

| <u>CAS Number</u> | <u>Wt %</u> | <u>Component Name</u> |
|-------------------|-------------|-----------------------|
|-------------------|-------------|-----------------------|

DOW CORNING CORPORATION
Material Safety Data Sheet

Page: 8 of 8

Version: 6.0

Revision Date: 2010/06/16

DOW CORNING(R) 995 SILICONE STRUCTURAL SEALANT, BLACK

| | | |
|------------|--------|---|
| PMN871176 | <=45.0 | Dimethyl siloxane, trimethoxysilyl-terminated |
| 471-34-1 | <=42.0 | Calcium carbonate |
| None | <=41.0 | Calcium carbonate treated with stearic acid |
| 68083-19-2 | <=6.2 | Dimethyl siloxane, dimethylvinyl-terminated |
| 1333-86-4 | <=1.1 | Carbon black |

16. OTHER INFORMATION

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark