

MSDS No.: **Revision No.: Revision Date:** Page:

259 010 08/17/04 1 of 2

MATERIAL SAFETY DATA SHEET

Product name:

FS-ONE High Performance Intumescent Firestop Sealant

Description:

One-part acrylic-based sealant

Supplier:

Hilti, Inc. P.O. Box 21148, Tulsa, OK 74121

Emergency # (Chem-Trec.):

1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (Other countries)

For:

AD&W

P O Box 910

WESTBROOK, ME 04098

INGREDIENTS AND EXPOSURE LIMITS

Abbreviations: PEL = OSHA Permissible Exposure Limit. **TLV** = ACGIH Threshold Limit Value. **C** = Ceiling. **STEL** = Short Term Exposure Limit. **NE** = None Established. **NA** = Not Applicable. **(T)** indicates "as total dust". **(R)** indicates "as respirable fraction". **(A)** indicates "as an aerosol". **mppcf** = million particles per cubic foot.

PHYSICAL DATA

	Red paste.	Odor:	Odorless.
Appearance:	Not determined.	Vapor Pressure:	23mbar @ 20C / 68F
Vapor Density: (air = 1)		VOC Content:	75.0 g/L
Boiling Point:	Not applicable.		Soluble.
Evaporation Rate:	Not applicable.	Solubility in Water:	Not determined.
Specific Gravity:	1.5	pH:	
	FIRE AND EX	Application bear section 7	

Flash Point:	
Extinguishing Media	:

Non-flammable.

Flammable Limits:

Not applicable.

Not applicable. Use extinguishing media as appropriate for surrounding fire.

Special Fire Fighting Procedures:

None known. Use a self-contained breathing apparatus when fighting fires involving chemicals.

Unusual Fire and Explosion Hazards:

None known. Thermal decomposition products can be formed such as oxides of carbon, sulfur, and phosphorous.

REACTIVITY DATA

Stability:

Stable.

Hazardous Polymerization:

Will not occur.

Incompatibility:

Strong acids, peroxides, and oxidizing agents.

Decomposition Products:

Thermal decomposition can yield CO and CO₂.

Conditions to Avoid:

None known.

HEALTH HAZARD DATA

Known Hazards:

None known.

Signs and Symptoms of Exposure:

Possibly irritating upon contact with the eyes or upon repeated contact with the skin.

Medical Conditions Aggravated by Exposure: Eye and skin conditions.

puter of Exposure:

Carcinogenicity:

Dermal.

IARC classifies crystalline silica (quartz sand) as Gp I based upon evidence among workers in industries where there has been long-term and chronic exposure (via inhalation) to silica dust; e.g. mining, quarry, stone crushing, refractory brick and pottery workers. This product does not pose a dust hazard; therefore, this classification is not relevant. Based upon the nature and intended use of this product, it does not pose an increased cancer risk to workers.

EMERGENCY AND FIRST AID PROCEDURES

Eyes:

Immediately flush with plenty of water. Call a physician if symptoms occur.

Skin:

Immediately wipe off material and wash with soap and water. Material can adhere to the skin. If material has adhered to the skin, use an abrasive containing hand cleaner. If material does not

come off, buff with a pumice stone.

Inhalation:

Move victim to fresh air if discomfort develops. Call a physician if symptoms persist.

Ingestion:

Seek medical attention. Do not induce vomiting unless directed by a physician. If large quantity was ingested, give 1 to 2 glasses of water to dilute. Never give anything by mouth to an

unconscious person.

Other:

Referral to a physician is recommended if there is any question about the seriousness of the

injury/exposure.

CONTROL MEASURES AND PERSONAL PROTECTIVE EQUIPMENT

Ventilation:

General (natural or mechanically induced fresh air movements).

Eye Protection:

Not required, however, safety glasses should be worn in most industrial settings.

Skin Protection:

Avoid skin contact. Cloth gloves are suitable for hand protection.

Respiratory Protection:

None normally required. Where ventilation is inadequate to control vapors, use a NIOSHapproved respirator with organic vapor cartridges. Never enter a confined space without an

appropriate air-supplied respirator.

PRECAUTIONS FOR SAFE HANDLING AND USE

Handling and Storing Precautions:

Store in a cool, dry area preferably between 40° and 77° F. Keep from freezing. Do not store in direct sunlight. Avoid contact with the eyes or skin. Practice good hygiene; i.e. always wash thoroughly after handling and before eating or smoking. For industrial use only. Keep out of reach of children. Follow label/use instructions.

Spill Procedures:

Immediately wipe away spilled material before it hardens. Place in a container for proper

disposal in accordance with all applicable local, state, or federal requirements.

REGULATORY INFORMATION

Hazard Communication:

This MSDS has been prepared in accordance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

HMIS Codes:

Health 1, Flammability 0, Reactivity 0, PPE B

DOT Shipping Name:

Not regulated.

IATA/ICAO Shipping Name:

Not regulated.

TSCA Inventory Status:

Chemical components listed on TSCA inventory.

SARA Title III, Section 313:

This product contains < 3% ethylene glycol (CAS 107-21-1) and 15% zinc borateoxide (re: zinc compounds) which are subject to reporting under Section 313 of SARA Title III (40 CFR Part 372).

EPA Waste Code(s):

Not regulated by EPA as a hazardous waste.

Waste Disposal Methods:

Consult with regulatory agencies or your corporate personnel for disposal methods that comply

with local, state, and federal safety, health and environmental regulations.

CONTACTS

Customer Service:

1 800 879 8000

Technical Service:

1 800 879 8000

Health / Safety:

Jerry Metcalf

Emergency # (Chem-Trec):

1 800 879 6000 (x6704)

1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.