



MATERIAL SAFETY DATA SHEET

Product name: Hilti Lithium-Ion batteries (Except B36/3.3 Li-Ion Battery)
Description: Rechargeable Lithium-Ion batteries for power tools
Supplier: Hilti, Inc. P.O. Box 21148, Tulsa, OK 74121
Emergency # (Chem-Trec.): 1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)

For: A D & W
P O Box 910
WESTBROOK, ME 04098

INGREDIENTS AND EXPOSURE LIMITS

This product is regarded as an "Article" by definition under OSHA Regulation, 29CFR 1910.1200(c). This product contains a positive electrode (lithium cobalt oxide), a negative electrode (graphite) and electrolyte (ethylene carbonate, diethyl carbonate and lithium hexafluorophosphate). The physical form of the product, however, precludes exposure to workers under normal conditions of use.

PHYSICAL DATA

Appearance:	Red/Black plastic case.	Odor:	Not applicable.
Vapor Density: (air = 1)	Not applicable.	Vapor Pressure:	Not applicable.
Boiling Point:	Not applicable.	VOC Content:	Not applicable.
Evaporation Rate:	Not applicable.	Solubility in Water:	Not applicable.
Specific Gravity:	Not determined.	pH:	Not determined.

FIRE AND EXPLOSION HAZARD DATA

Flash Point:	Not applicable.	Flammable Limits:	Not applicable.
Extinguishing Media:	Carbon Dioxide, Dry Chemical, Foam, Water.		
Special Fire Fighting Procedures:	None known. Always use a self-contained breathing apparatus when fighting fires involving chemicals.		
Unusual Fire and Explosion Hazards:	None expected.		

REACTIVITY DATA

Hazardous Polymerization:	Will not occur.	Stability:	Stable.
Incompatibility:	Strong oxidizers/strong acids.		
Decomposition Products:	Thermal decomposition can yield toxic and acrid gases.		
Conditions to Avoid:	See "Handling and Storing Precautions" below.		

HEALTH HAZARD DATA

Known Hazards:	None known.
Signs and Symptoms of Exposure:	None anticipated.
Routes of Exposure:	None anticipated from proper use of this product.
Carcinogenicity:	Not applicable. See spill procedures.
Medical Conditions Aggravated by Exposure:	None expected.

EMERGENCY AND FIRST AID PROCEDURES

Under normal conditions of use, no exposure(s) should occur. The Emergency and First Aid Procedures are only applicable where there has been an exposure to electrolyte which has leaked from a damaged battery

Eyes:	Flush with plenty of water. Contact a physician if symptoms occur.
Skin:	Wash with soap and water. Contact a physician if symptoms occur.
Inhalation:	Move victim to fresh air. Contact a physician if symptoms persist.
Ingestion:	Contact a physician immediately.
Other:	Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure.

CONTROL MEASURES AND PERSONAL PROTECTIVE EQUIPMENT

Ventilation:	General (natural or mechanically induced fresh air movements).
Eye Protection:	Not required for handling the battery pack; however, safety glasses with side shields recommended while using most powered hand tools.
Skin Protection:	Not required
Respiratory Protection:	Not normally required. However, in some instances, dusts generated while drilling/sawing may necessitate the use of respiratory protection.

PRECAUTIONS FOR SAFE HANDLING AND USE

Handling and Storing Precautions:	Store in a cool dry place less than 95° F. Exposure to excessive heat and humidity and storage above 100° F will shorten the shelf life of this product. Keep out of reach of children. For industrial use only.
Spill Procedures:	If the battery integrity is destroyed by accident, (for example crushing) and the contents are released, do not touch spilled material. Take up with sand or other absorbent and place in container for disposal. Contact with battery contents may cause skin irritation and/or corrosive eye damage. If skin contact occurs, wash affected areas thoroughly with soap and water. Get medical attention if irritation develops. If eye contact occurs, flush thoroughly with running water for at least 15 minutes, while holding eyelids open. Get prompt medical attention.


REGULATORY INFORMATION

Hazard Communication:	This product is regarded as an "Article" by OSHA definition.
HMIS Codes:	Health 0, Flammability 0, Reactivity 0, PPE A
DOT Shipping Name:	Not regulated.
IATA Shipping Name:	Not regulated.
TSCA Inventory Status:	Chemical components listed on TSCA inventory.
SARA Title III, Section 313:	This product is considered to be an "Article", therefore, it is not subject to reporting under Section 313 of SARA Title III (40 CFR Part 372).
EPA Waste Code(s):	N/A
Waste Disposal Methods:	Batteries may be returned to Hilti by contacting the local salesperson, returning it to the local Hilti Center, or calling the toll free number (1-800-879-8000) where a Customer Service Representative will provide return instructions. DO NOT DISPOSE IN THE TRASH. Place tape over any exposed terminals to prevent inadvertent short-circuit during transportation.

CONTACTS

Customer Service:	1 800 879 8000	Technical Service:	1 800 879 8000
Health / Safety:	1 800 879 6000	Jerry Metcalf	(x3704)
Emergency # (Chem-Trec):	1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)		

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.



MATERIAL SAFETY DATA SHEET

Product name: Safety Boosters
Description: 22, 25, and 27 caliber blank cartridges for powder actuated fastening tools
Supplier: Hilti, Inc. P.O. Box 21148, Tulsa, OK 74121; phone 1800 879 8000
Emergency # (Chem-Trec.): 1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)

INGREDIENTS AND EXPOSURE LIMITS

Ingredients:	CAS Number:	TLV:	PEL:	STEL:
Nitroglycerin	00055-63-0	0.46 mg/m ³ (S)	NE	2 mg/m ³ (S)
Nitrocellulose	09004-70-0	NE	NE	NE
Lead styphnate	15245-44-0	0.05 mg/m ³ *	0.05 mg/m ³ *	NE
Barium nitrate	10022-31-8	0.5 mg/m ³	0.5 mg/m ³	NE
Tetracene	00109-27-3	NE	NE	NE

Abbreviations / Symbols: * exposure limit for metallic lead. **NE** = None Established. **NA** = Not Applicable. **(S)** indicates exposure should be controlled for the cutaneous routes including the mucous membranes, eyes, and skin. Airborne exposures as well as direct contact must be considered.

PHYSICAL DATA

Appearance:	Blank brass cartridges.	Odor:	None.
Vapor Density: (air = 1)	Not applicable.	Vapor Pressure:	Not applicable.
Boiling Point:	Not applicable.	VOC Content:	Not applicable.
Evaporation Rate:	Not applicable.	Solubility in Water:	Not applicable.
Specific Gravity:	Not applicable.	pH:	Not applicable.

FIRE AND EXPLOSION HAZARD DATA

Flash Point:	Not applicable.	Flammable Limits:	Not applicable.
Extinguishing Media:	Water.		
Special Fire Fighting Procedures:	Flood area with water or keep cartridges cool with water spray.		
Unusual Fire and Explosion Hazards:	Cartridges can blast if exposed to temperatures > 160°C. Mass detonation will not occur.		

REACTIVITY DATA

Hazardous Polymerization:	Will not occur.	Stability:	Stable.
Incompatibility:	Strong acids and oxidizing agents.		
Decomposition Products:	Oxides of nitrogen, oxides of carbon, acrid fumes and lead oxide.		
Conditions to Avoid:	Acids, excessive heat, crushing, and electrical currents.		

HEALTH HAZARD DATA

Known Hazards:	OSHA has established an action level of 0.03 mg/m ³ for lead. Exposures that exceed recommended limits for lead may be possible under certain conditions such as excessive firing with little air movement and/or firing in small enclosed work areas. Chronic (long-term) overexposure to lead can result in damage to blood-forming, nervous, urinary and reproductive systems.
Signs and Symptoms of Exposure:	Excessive exposure to gases might cause irritation to the eyes, skin, and respiratory system. Adverse health effects are not expected from acute exposure to fumes and gases; however, adequate ventilation, personal protective equipment, and/or good personal hygiene practices are essential to keep exposure to a minimum.
Routes of Exposure:	Dermal. Inhalation.
Carcinogenicity:	Organic lead compounds are not classified by IARC or NTP as carcinogens. Lead styphnate is converted to metallic lead and lead oxide during combustion. Metallic lead and lead oxide have not been tested adequately.
Medical Conditions Aggravated by Exposure:	None anticipated.

EMERGENCY AND FIRST AID PROCEDURES

Eyes:	If irritation occurs, flush with plenty of water. Consult a physician if symptoms persist.
Skin:	Practice good hygiene; i.e. wash with soap and water after using and before smoking/eating.
Inhalation:	Move victim to fresh air. Get medical attention if symptoms persist.
Ingestion:	Get immediate medical attention.
Other:	Referral to a physician is recommended if there is any question about the seriousness of the injury/exposure.

CONTROL MEASURES AND PERSONAL PROTECTIVE EQUIPMENT

Ventilation:	General (i.e., natural or mechanically induced fresh air movements that maintain vapor concentrations below recommended exposure limits).
Eye Protection:	Suitable safety glasses with side-shields, or safety goggles.
Skin Protection:	Cleaning powder actuated tools can result in some exposure to lead compounds. Impermeable gloves are recommended. Wash hands thoroughly when finished and before eating or smoking.
Respiratory Protection:	Not normally required. Where air movement is inadequate to maintain exposure below recommended levels, wear a high efficiency particulate respirator.
Other:	Hearing protection should be worn when firing powder actuated tools

PRECAUTIONS FOR SAFE HANDLING AND USE

Handling and Storing Precautions:	Store in a cool dry place. Do not crush or drop. Keep away from excessive heat, electrical current, strong acids and oxidizers. NFPA 495 requires 15 feet separation (or 1-hour firewall) from flammable liquids, flammable solids, and oxidizers. For industrial use only. Keep out of reach of children. Use with adequate ventilation. Practice good hygiene; i.e. wash after using and before eating or smoking.
Other Precautions::	Use only in powder actuated tools designed to handle these boosters. Construction industry employees must be properly trained as prescribed by OSHA regulations 29 CFR 1926.302 (e). All employees should be familiar with the safe operating procedures and requirements for powder operated tools as described in ANSI A10.3 and OSHA 29 CFR 1910.243 (d).

REGULATORY INFORMATION

Hazard Communication:	This MSDS has been prepared in accordance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200.
HMIS Codes:	Health 1, Flammability 1, Reactivity 3, PPE B (Glasses, Gloves)
DOT Shipping Name:	Limited Quantity - LQ
ICAO / IATA Shipping Name:	Cartridges. Power device, Class 1.4S, UN 0323
TSCA Inventory Status:	Chemical components listed on TSCA inventory.
SARA Title III, Section 313:	This product contains < 1% lead styphnate (CAS No. 15245-44-0), < 0.1% barium nitrate (CAS No. 10022-31-8), and 5 - 11% nitroglycerin (CAS No. 55-63-0) which are subject to the reporting according to Section 313 of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.
Waste Disposal Methods:	Misfires should be stored in a closed container until disposal or as otherwise required by local, state, and federal safety, health and environmental regulations. The recommended disposal method is an explosives incinerator.
EPA Waste Code(s):	D008

CONTACTS

Customer Service:	1 800 879 8000
Technical Service:	1 800 879 8000
Health / Safety:	1 800 879 6000 Jerry Metcalf (x1003704)
Emergency # (Chem-Trec):	1 800 424 9300 (USA, PR, Virgin Islands, Canada); 001 703 527 3887 (other countries)

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided.